



GENERAL DESCRIPTION

Junckers BasePrime is a quick-drying primer which in combination with Junckers solvent based or water based lacquers is suitable for sanded and untreated wooden floors, including most exotic wood species.

The primer gives light-coloured wood species a golden appearance.

Junckers BasePrime should only be used as the sealing coat for the wood fibres. For priming of ammonia-treated wood Junckers PreLak or Junckers ProSeal is recommended.

PRODUCT DESCRIPTION

Product: Priming lacquer based on alcohol-solvent.

Package sizes: 5 litre and 10 litre.

Appearance: Colourless.

TECHNICAL DATA

Coverage: 10 m² per litre.

Before use: Stir well before use.

Application tools: Brush or short-pile varnishing roller.
Do not apply by spraying.

Substrate temperature: Minimum 15° C.

Dilution: Delivered ready for use. Dilution is not recommended.

Drying time:
Dry to touch after approx. 15 min. at 20° C and 50 % RH.

Cleaning of tools: White spirit.

Storage: Lasts for 2 years if unopened and stored at 20° C. Not to be exposed to temperatures above 40° C.

SYSTEM RECOMMENDATIONS

High traffic areas:

1 coat Junckers BasePrime 10 m²/litre
+ 2 coats Junckers HP Commercial 10m²/litre

or

1 coat Junckers BasePrime 10 m²/litre
+ 2 coats Junckers STRONG 10 m²/litre

Low traffic areas:

1 coat Junckers BasePrime 10 m²/litre
+ 2 coats Junckers ProTech 10 m²/litre

or

1 coat Junckers BasePrime 10 m²/litre
+ 2 coats Junckers ProFinish 10 m²/litre

Sport areas:

1 coat Junckers BasePrime 10 m² litre
+ 2 coats Junckers HP SPORT 10m²/litre

DIRECTION FOR USE

Untreated/sanded floors:

The surface should be clean, dry and free from dust, wax, grease, polish etc. Machine sand the floor as advised under "Previously sealed floors" to remove dirt and irregularities.

The last sanding should be carried out by using minimum grit 100-120 before applying Junckers BasePrime. Thoroughly clean off the sanding dust (e.g. by vacuuming).

Apply Junckers BasePrime in an even layer with a varnishing roller or brush. Leave to dry properly before sanding and applying the finishing coats of lacquer according to one of Junckers system recommendations.

Previously sealed floors:

Machine sand before applying Junckers BasePrime. Use grit 24-36 to strip old coats. Then remove abrasion marks with grit 60-80. Finally, use grit 100-120 to obtain a completely smooth surface. Vacuum sanding dust and prime the floor as described under "Untreated/sanded floors".

IMPORTANT

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

FURTHER INFORMATION

Products:

F 4.2 - Junckers ProFinish
F 5.1 - Junckers STRONG
F 6.2 - Junckers ProTech
F 8.2 - Junckers HP SPORT
F 8.5 - Junckers HP Commercial