



General Description

Junckers Rustic Oil colour is an oil product for staining of untreated table tops, and wooden floors.

Technical Data

Product:	Coloured drying urethane oil in low odor solvent.
Package sizes:	0.75 litre, 2.5 litre and 5 litre.
Appearance:	Coloured liquid that dries to a transparent coloured surface.
Colours:	White Black Anthracite grey/SpicyPepper DarkCoco HotSalsa Mahogany/SylvaRed Nut/SylvaKet RawSugar SmoothRum Walnut WildHazel
Coverage:	10-50 m ² per litre depending on the wood structure and absorbance.
Application tools:	All surfaces: Cloth, brush or lambs wool applicator. Floors: A buffing machine mounted with a cloth covered pad, helps spreading and removal of surplus liquid.
Substrate temperature:	Minimum 5°C.
Dilution:	Delivered ready for use. Dilution is not recommended.
Drying time:	16-24 hours before applying the finishing oil. Ready for use 24 hours after the finishing treatment. Fully cured after 3 days.
Cleaning of tools:	White spirit or Junckers Thinner 008 .
Storage:	2 years if unopened and stored at 20°C. Once opened the oil will start to form a skin and may harden in the can.

System Recommendations

Floors and table tops:	1 coat Junckers Rustic Oil colour + 2 coats Junckers Rustic Oil clear or colour
Floors:	
High traffic areas:	1 coat Junckers Rustic Oil colour + 2 coats Junckers High Performance Commercial .
Low traffic areas:	1 coat Junckers Rustic Oil colour + 2 coats Junckers Profinish

Directions for Use

Staining of untreated/sanded wood:

- 1) Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Unevenness, dirt and discolouration can be removed by sanding in the direction of the grain. Final sanding must be with sandpaper grit 100-120. Vacuum sanding dust.
- 2) Moisten the surface with a damp cloth. Be sure that the floor is evenly and visibly wetted to avoid a patchy appearance of the staining. Then leave to dry 10-15 minutes.
- 3) Apply **Junckers Rustic Oil colour** in excessive amounts. Allow the wood to absorb liquid until full saturation and matt areas no longer appear. After 30 - 45 minutes the saturation is complete. Remove immediately any excess oil using a dry cloth to leave a matt, even colour. Any remains of oil will create glossy and tacky spots.

Floors:

Larger areas are recommended to be divided into smaller areas of 10-25 m². Always keep a wet edge between areas.

Finishing with Junckers Rustic Oil clear or colour:

- 1) Screen with a black pad and remove the dust.
- 2) Depending on colour intensity, finish with either clear or coloured oil.

The surface is protected by **Junckers Rustic Oil clear or colour** by applying 2 thin coats followed by drying, all according to the recommendations. Polish until an even appearance is obtained.

Finishing with lacquer - Floors:

Higher wearability of the floor can be obtained by finishing with lacquer. Choose one of Junckers lacquers according to the recommended systems.

- 1) Screen with a black pad and remove the dust.
- 2) Apply one coat of lacquer. Leave to dry 24 hours.
- 3) Sand with 180-220 grit sandpaper. Vacuum sanding dust. Remove sanding dust with a vacuum cleaner and wipe away with a damp cloth.
- 4) Apply the final coat of lacquer. Leave to dry until fully cured.

Cleaning and maintenance – oiled surfaces:

Use **Junckers Rustic Oil clear or colour** as surface refresher if any sign of wear appear. Maintain with **Junckers Rustic Top Oil**.

Oiled surfaces worn through:

Sanding to untreated wood of the full area, followed by a new application of stain and finish is necessary to obtain an even appearance.

Important!

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

Important!

Stir well before use.

Important!

Do not cover the surface by i.e. carpets or rugs before the oil is fully cured.

Further information

Products:

- F 2.1 - **Junckers Rustic Oil clear**
- F 2.5 - **Junckers Thinner 008**
- F 2.7 - **Junckers Rustic Top Oil**
- F.4.2 - **Junckers Profinish**
- F 8.5 - **Junckers High Performance Commercial**