

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** VOEGENKIT FILLER MASTIC 7500
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation** Filler and surfacer
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
WAKOL GmbH
Bottenbacher Str. 30
66954 Pirmasens
thomas.wieland@wakol.de
- +49 (0)6331 8001 144
- **Informing department:** Industrial Safety Department
- **Emergency telephone number:** During business hours: Industrial Safety Department; +49 (0) 6331 8001 144

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  Xi; Irritant
- R36: Irritating to eyes.
-  F; Highly flammable
- R11: Highly flammable.
- R67: Vapours may cause drowsiness and dizziness.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
-   Xi Irritant
F Highly flammable
- **Risk phrases:**
11 Highly flammable.
36 Irritating to eyes.
67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**
2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
29 Do not empty into drains.
33 Take precautionary measures against static discharges.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.

(Contd. on page 2)

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

Trade name: **VOEGENKIT FILLER MASTIC 7500**

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-64-1	acetone	50-100%
EINECS: 200-662-2	Xi R36; F R11 R66-67	
CAS: 9004-70-0	cellulose nitrate	2.5-<10%
	E R3	
CAS: 67-63-0	propan-2-ol	1.0-<5%
EINECS: 200-661-7	Xi R36; F R11 R67	
CAS: 64-17-5	ethanol	1.0-<2.5%
EINECS: 200-578-6	F R11	

- **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation** Supply fresh air.
- **After skin contact** Generally the product does not irritate the skin.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing** Do not induce vomiting; call for medical help immediately.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation

(Contd. on page 3)

GB

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

Trade name: VOEGENKIT FILLER MASTIC 7500

(Contd. of page 2)

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

· **DNELs**

67-64-1 acetone

Oral DNEL 62 mg/kg/day (general population (long-term))

Dermal DNEL 62 mg/kg/day (general population (long-term))

186 mg/kg/day (workwr (long-term))

Inhalative DNEL 200 mg/m³ (general population (long-term))

(Contd. on page 4)

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

Trade name: VOEGENKIT FILLER MASTIC 7500

(Contd. of page 3)

2420 mg/m³ (workers (short-term))1210 mg/m³ (workwr (long-term))· **PNECs****67-64-1 acetone**

PNEC 10.6 mg/l (freshwater)

1.06 mg/l (sea water)

21 mg/l (water - partially release)

29.5 mg/kg (soil)

3.04 mg/kg (sediment (sea water))

30.4 mg/kg (sediment (freshwater))

100 mg/l (STP)

· **Additional information:** The lists valid during the making were used as basis.· **Exposure controls**· **Personal protective equipment**· **General protective and hygienic measures** Wash hands before breaks and at the end of work.· **Breathing equipment:** Not necessary if room is well-ventilated.· **Protection of hands:** Preventive skin protection by use of skin-protecting agents is recommended.· **Eye protection:** Safety glasses

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Fluid**Colour:** Colourless· **Smell:** Characteristic· **Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** 56 °C· **Flash point:** -18 °C· **Ignition temperature:** 540 °C· **Self-inflammability:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Critical values for explosion:****Lower:** 2.1 Vol %**Upper:** 13.0 Vol %· **Steam pressure at 20 °C:** 247 mbar· **Density at 20 °C** 0.80 g/cm³ (EN ISO 2811-1)· **Solubility in / Miscibility with****Water:** Not miscible or difficult to mix.· **Viscosity:****dynamic at 20 °C:** 1200 mPas (ISO 2555)· **Solvent content:****VOC** 87.38 %

(Contd. on page 5)

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

Trade name: VOEGENKIT FILLER MASTIC 7500

· **Other information**

No further relevant information available.

(Contd. of page 4)

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
 - **LD/LC50 values that are relevant for classification:**
- 67-64-1 acetone**
- Oral LD50 5800 mg/kg (rat) (OECD RL 401)
- Dermal LD50 >15800 mg/kg (rat)
- Inhalative LC50/4h 76 mg/l (rat)
- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
 - **Sensitization:** No sensitizing effects known.
 - **Additional toxicological information:**
- The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
- Irritant

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:**
- 67-64-1 acetone**
- EC5/16h 1700 mg/l (*Pseudomonas putida*)
- EC5/72h 28 mg/l (*Entosiphon sulcatum*)
- EC5/8d 530 mg/l (*Microcystis aerruginosa*)
- EC50/18h 12600-12700 mg/l (*Daphnia magna*)
- EC50/48h 6100 mg/l (*Daphnia magna*)
- EC50/96h 8300 mg/l (*Lepomis macrochirus*)
- LC50/48h 12600 mg/l (*Daphnia magna*)
- 11300 mg/l (*Leuciscus idus*)
- LC50/96h 11300 mg/l (*Leuciscus idus*) (DIN 38412 T.15)
- 5540 mg/l (*Oncorhynchus mykiss*)
- 8300 mg/l (*Lepomis macrochirus*)
- NOEC/16h 1700 mg/l (*Pseudomonas putida*)
- NOEC/48h 4740 mg/l (*Selenastrum capricornutum*)

(Contd. on page 6)

GB

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

Trade name: VOEGENKIT FILLER MASTIC 7500

(Contd. of page 5)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must be specially treated adhering to official regulations.
- **European waste catalogue**
08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN1133
- **UN proper shipping name**
- **ADR** 1133 ADHESIVES, special provision 640H
- **IMDG, IATA** ADHESIVES
- **Transport hazard class(es)**
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3
- **Packing group**
- **ADR, IMDG, IATA** III
- **Environmental hazards:**
- **Marine pollutant:** no
- **Special precautions for user** Warning: Flammable liquids.
- **Kemler Number:** 33
- **EMS Number:** F-E,S-D
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 7)

Material safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2012

Version number 14

Revision: 31.10.2012

Trade name: VOEGENKIT FILLER MASTIC 7500

(Contd. of page 6)

· Transport/Additional information:

· ADR

- | | |
|------------------------------------|-----|
| · Excepted quantities (EQ): | E1 |
| · Limited quantities (LQ) | 5L |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **VOC:**
- **VOC (EU) 699.0 g/l**
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- R11 Highly flammable.
- R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.
- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

- **Department issuing data specification sheet:** Industrial Safety Department.
- **Contact:** Dr. Thomas Wieland