

# TECHNICAL INFORMATION

## PrimaSeal Plus



**NEW**

Alcohol-based primer for wooden floors.

- Simple and safe application
- Excellent blocking of wood ingredients and old contamination
- Intensifies the colour of the wood
- Good price/performance ratio

### Range of use:

Suitable for virtually all types of European and exotic timber. Note the LOBA wood types list, which can be found at [www.loba.de](http://www.loba.de). If in doubt, consult the factory. The side-bonding effect of waterborne finishes is reduced. No block bonding occurs with parquet or wooden flooring that has been properly laid and bonded or secured with shear-resistant adhesive.

## Technical Data

### Art.-no.

11033

5 l

10 l



4

-



128

40

Storage and transportation

12 months of storage stability. Not sensitive to frost.

GISCODE

G1

## Application

- The surface must be sanded properly, wood moisture content max. 12%.
- The floor must be dry and free from any old coatings, oil, grease, wax, silicone, sanding dust and other contaminants. Room temperature +15°C to +25°C, relative humidity 40% to 75%, material temperature +18°C to +25°C. Ensure working areas are adequately ventilated.
- Transfer material to a LOBATOOL varnish bucket before applying.
- Stir the material well.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at [www.wingis-online.de](http://www.wingis-online.de).

### Thinner

The product is supplied ready for use and must not be diluted!

### Application tool/application rate

LOBATOOL roller Universal / 100 - 120 ml/m<sup>2</sup> (8-10 m<sup>2</sup>/l).

3/2017



# TECHNICAL INFORMATION

# PrimaSeal Plus



## Application

---

### Intermediate sanding

Do not intermediate-sand the primer.

### Drying time

- The earliest the floor can be varnished over in the case of roller applications is approx. 60 to 90 minutes.
- If there are drying delays, wait until completely dry.

### For varnishing over suitable finishes:

Normal traffic:

- WS Life.

Up to heavy traffic:

- WS EasyFinish.
- WS Viva.

Up to very heavy traffic:

- 2K Supra A.T..
- WS 2K Duo.

### Application for parquet and wooden flooring:

- Prepare the substrate properly.
- Roller on the primer generously.
- Drying.
- Roll on LOBADUR® waterborne finish.



# TECHNICAL INFORMATION

# PrimaSeal Plus



## General guidelines

**Cleaning of tools:** Clean tools with solvents such as brush cleaner.

**Drying time:** The indicated drying times are valid for +20°C and 55% to 65% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

**Safety notes:** Flammable solvent vapours emerge during the drying process when working with products containing high quantities of solvents. As a result, fire, naked light, welding, smoking and so on are prohibited in the immediate vicinity of such products. Ventilate working areas and storage rooms well. Electrical equipment in workrooms and ancillary rooms must be switched off in sufficient time to ensure that they are cold when work begins. Any spark generation, including on electrical equipment, must be avoided. Keep material containers tightly closed. Solvent sensitive components, plants or animals (fish tanks) must be removed from areas at risk of exposure to solvent vapours.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to normal conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

3/2017

