Page 1/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2014

Classification according to

1999/45/EC

Directive 67/548/EEC or Directive

Version number 13

Revision: 17.01.2014

GB

1.1 Product identifier	
Trade name:	3062 Osmo Polyx®-Oil Original, clear matt
1.2 Relevant identified uses of	of the
substance or mixture and use	25
advised against	No further relevant information available.
Application of the substance	/ the
preparation	Paint
	Coating compound/ Surface coating/ paint
1.3 Details of the supplier of	the safety data sheet
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG
	Affhüppen Esch 12
	D-48231 Warendorf
Further information obtainal	ble
from:	Product safety department
	Phone: +49 (0) 251 / 692 - 188
	Fax: +49 (0) 251 / 692 - 462
	e-mail: helmut.starp@osmo.de
1.4 Emergency telephone	
number:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in Germ
numeen	and English

particular hazards for human environment:	The product does not have to be labelled due to the calculation procedure of the
	"General Classification guideline for preparations of the EU" in the latest valid version.
Classification system:	The classification is according to the latest editions of the EU-lists and extended by company and literature data.
2.2 Label elements	
Labelling according to Regula	ution
(EC) No 1272/2008	Void
Hazard pictograms	Void
Signal word	Void
Hazard statements	Void
Precautionary statements	Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.
	(Contd. on page 2)

Not applicable.



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

	(Contd. of page 1)
	P101 If medical advice is needed, have product container or label at hand.
	P102 Keep out of reach of children.
	P262 Do not get in eyes, on skin, or on clothing.
	P271 Use only outdoors or in a well-ventilated area.
	P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.
Additional information:	Observe the general safety regulations when handling chemicals.
-	Always wear a dust mask when sanding.
	Contains 2-butanonoxime. May produce an allergic reaction.
	Safety data sheet available on request.
2.3 Other hazards	
Results of PBT and vPvB ass	essment
PBT:	Not applicable.
vPvB:	Not applicable.

SECTION 3: Composition/information on ingredients

3.2	Mixtures
-----	----------

Description:	Mixture of substances listed below with nonhazardous additions.	
Dangerous components:		
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
Index number: 649-327-00-6	🗙 Xn R65	
Reg.nr.: 01-2119457273-39	R66	
	🐼 Asp. Tox. 1, H304	-
Additional information:	For the wording of the listed risk phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measu	ires
General information:	Take affected persons out into the fresh air.
	Immediately remove any clothing soiled by the product.
After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult
	doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	Do not induce vomiting; call for medical help immediately.
4.2 Most important symptoms and	d
effects, both acute and delayed	Dizziness
	Headache
	(Contd. on page 3)

- GB

Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 17.01.2014

Version number 13

(Contd. of page 2)

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant
	foam.
For safety reasons unsuitable	
extinguishing agents:	Water with full jet
5.2 Special hazards arising from	
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters	
Protective equipment:	Mouth respiratory protective device.
Additional information	Cool endangered receptacles with water spray.
	Dispose of fire debris and contaminated fire fighting water in accordance with official
	regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and	
emergency procedures	Ensure adequate ventilation
	Keep away from ignition sources.
6.2 Environmental precautions:	Do not allow to enter sewers/ surface or ground water.
	Inform respective authorities in case of seepage into water course or sewage system.
6.3 Methods and material for	
containment and cleaning up:	Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
6.4 Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handle	<i>ing</i> Keep away from heat and direct sunlight.	
	Use only in well ventilated areas.	
	Keep receptacles tightly sealed.	
	Prevent formation of aerosols.	
Information about fire - and		
explosion protection:	Keep ignition sources away - Do not smoke.	
		(Contd. on page 4)

- GB



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt (Contd. of page 3) 7.2 Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: Store only in the original receptacle. Store in a cool location. Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions). Do not store together with oxidizing and acidic materials. Further information about Store in cool, dry conditions in well sealed receptacles. storage conditions: Keep container tightly sealed. No further relevant information available. 7.3 Specific end use(s) **SECTION 8: Exposure controls/personal protection** Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 64742-48-9 aliphatic hydrocarbons, C10-C13 TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm Source: UK SIA Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Do not carry product impregnated cleaning cloths in trouser pockets. **Respiratory protection:** Not necessary if room is well-ventilated. Use suitable respiratory protective device only when aerosol or mist is formed. Short term filter device: Filter A/P2 **Protection of hands:** Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation To avoid skin problems reduce the wearing of gloves to the required minimum. Material of gloves Nitrile rubber, NBR (Contd. on page 5)

- GB



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

	(Contd. of page 4)
Penetration time of glove materia	<i>l</i> The exact break trough time has to be found out by the manufacturer of the protective
	gloves and has to be observed.
For the permanent contact gloves	
made of the following materials	
are suitable:	Nitrile rubber, NBR
	Recommended thickness of the material: ≥ 0.4 mm
	For the mixture of chemicals mentioned below the penetration time has to be at least
	480 minutes (Permeation according to EN 374 Part 3: Level 6).
For the permanent contact of a	
maximum of 15 minutes gloves	
made of the following materials	
are suitable:	Nitrile rubber, NBR
Eye protection:	If risk of splashing:
	Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side
	protection)
Body protection:	Protective work clothing
. –	

SECTION 9: Physical and chemical properties

9.1 Information on basic physica General Information	
Appearance:	
Form:	Viscous
Colour:	Yellowish
Odour:	Mild
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 180 °C
Flash point:	> 63 °C (DIN EN ISO 2719)
Ignition temperature:	240 °C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures a possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	6.0 Vol %
Density at 20 °C:	0.92-0.95 g/cm ³

GB -



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

GB

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Viscosity:	
Dynamic at 20 °C:	150-180 mPas
Kinematic at 20 °C:	25-35 s (DIN 53211/4mm)
Solvent content:	
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))
9.2 Other information	No further relevant information available.
10.1 Reactivity	d reactivity
SECTION 10: Stability an 10.1 Reactivity 10.2 Chemical stability	d reactivity
	d reactivity
10.1 Reactivity 10.2 Chemical stability	<i>d reactivity</i> No decomposition if used according to specifications.
10.1 Reactivity 10.2 Chemical stability Thermal decomposition /	
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided:	
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous	No decomposition if used according to specifications.
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous reactions	No decomposition if used according to specifications. Reacts with fabric soaked in the product (e.g. cleaning wool).
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous reactions 10.4 Conditions to avoid	No decomposition if used according to specifications. Reacts with fabric soaked in the product (e.g. cleaning wool). No further relevant information available.
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous reactions 10.4 Conditions to avoid 10.5 Incompatible materials:	No decomposition if used according to specifications. Reacts with fabric soaked in the product (e.g. cleaning wool). No further relevant information available.
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous reactions 10.4 Conditions to avoid 10.5 Incompatible materials: 10.6 Hazardous decomposition	No decomposition if used according to specifications. Reacts with fabric soaked in the product (e.g. cleaning wool). No further relevant information available. No further relevant information available.
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous reactions 10.4 Conditions to avoid 10.5 Incompatible materials: 10.6 Hazardous decomposition	No decomposition if used according to specifications. Reacts with fabric soaked in the product (e.g. cleaning wool). No further relevant information available. No further relevant information available. Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)
10.1 Reactivity 10.2 Chemical stability Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous reactions 10.4 Conditions to avoid 10.5 Incompatible materials: 10.6 Hazardous decomposition products:	No decomposition if used according to specifications. Reacts with fabric soaked in the product (e.g. cleaning wool). No further relevant information available. No further relevant information available. Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

64742-48	-9 aliphati	hydrocarbons, C10-C13	
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)	
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)	
Inhalative	LC50 / 4h	> 5 mg/l (rat) (OECD 403)	
96-29-7 2	-butanono	kime	
Oral	LD50	3700 mg/kg (rat)	
Dermal	LD50	200-2000 mg/kg (rat)	
			(Contd. on pa



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

Primary irritant effect: on the skin:	At long or repeated contact with skin it may cause dermatitis due to the degreasi
on the skin:	effect of the solvent.
on the eye:	Irritating effect.
Sensitization:	Sensitizing effect by skin contact is possible by prolonged exposure.
Additional toxicological	benshizing effect of skin contact is possible of protonged exposure.
information:	The product is not subject to classification according to the calculation method of
·	General EU Classification Guidelines for Preparations as issued in the latest version.
	When used and handled according to specifications, the product does not have a
	harmful effects to our experience and the information provided to us.
Sensitisation	Contains 2-butanonoxime. May produce an allergic reaction.

Aquatic toxicity: 64742-48-9 aliphatic hydrocarbons, C10-C13 EC50 / 48h > 1000 mg/l (daphnia) (OECD 202) EC50/72h > 1000 mg/l (algae) (OECD 201) LC50 / 96h > 1000 mg/l (fish) (OECD 203) 96-29-7 2-butanonoxime EC50 / 48h 201 mg/l (daphnia) IC50 / 72h 11.8 mg/l (algae) LC50 / 96h >100 mg/l (fish) 12.2 Persistence and degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available. No further relevant information available. 12.4 Mobility in soil Additional ecological information: General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system. 12.5 Results of PBT and vPvB assessment **PBT**: Not applicable. vPvB: Not applicable. No further relevant information available. 12.6 Other adverse effects

(Contd. on page 8)

GB -



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances 15 01 10 packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging: **Recommendation:** Recommended cleansing agents: Solvent naphtha

Disposal must be made according to official regulations.

SECTION 14: Transport information				
14.1 UN-Number				
ADR, ADN, IMDG, IATA	Void			
14.2 UN proper shipping name				
ADR, ADN, IMDG, IATA	Void			
14.3 Transport hazard class(es)				
ADR, ADN, IMDG, IATA				
Class	Void			
14.4 Packing group				
ADR, IMDG, IATA	Void			
14.5 Environmental hazards:				
Marine pollutant:	No			
14.6 Special precautions for user	Not applicable.			
14.7 Transport in bulk according to Anne	ex II of			
MARPOL73/78 and the IBC Code	Not applicable.			
UN "Model Regulation":	-			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:	
GISBAU-Code	GISCODE: Ö60
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))

(Contd. on page 9)



Printing date 17.01.2014

Version number 13

Revision: 17.01.2014

(Contd. of page 8)

Trade name: 3062 Osmo Polyx®-Oil Original, clear matt

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This information is based on our	present knowledge. However, this shall not constitute a guarantee for any specific produ	
features and shall not establish a l	egally valid contractual relationship.	
Relevant phrases	H304 May be fatal if swallowed and enters airways.	
	R65 Harmful: may cause lung damage if swallowed.	
	R66 Repeated exposure may cause skin dryness or cracking.	
Department issuing MSDS:	product safety department	
Contact:	Hr. Dr. Starp	
Abbreviations and acronyms:	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de	
,	(Regulations Concerning the International Transport of Dangerous Goods by Rail)	
	ICAO: International Civil Aviation Organization	
	ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreeme	
	concerning the International Carriage of Dangerous Goods by Road)	
	IMDG: International Maritime Code for Dangerous Goods	
	IATA: International Air Transport Association	
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals	
	EINECS: European Inventory of Existing Commercial Chemical Substances	
	ELINCS: European List of Notified Chemical Substances	
	CAS: Chemical Abstracts Service (division of the American Chemical Society)	
	VOC: Volatile Organic Compounds (USA, EU)	
	LC50: Lethal concentration, 50 percent	
	LD50: Lethal dose, 50 percent	