Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

Jika

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name :

Sika® Primer MB (A)

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ United Kingdom
Telephone no.	:	01707 394444
Fax no.	:	01707 329129
e-mail address of person responsible for this SDS	:	EHS@uk.sika.com
Emergency telephone number	:	-

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	:	Xi; R36/38 R43 N; R51/53
Human health hazards	:	Irritating to eyes and skin. May cause sensitisation by skin contact.
Environmental hazards	:	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Additional warning phrases	:	Contains epoxy constituents. See information supplied by the manufacturer.
On a section 44 feature data		disformation on boolth offects and expertence

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ Characteristics

: Modified epoxi resin

Ingredient name	CAS number	%	EC number	Classification	
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)		50-75	500-033-5	Xi; R36/38 R43 N; R51/53	[1]
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	5-10	500-006-8	Xi; R36/38 R43 N; R51/53	[1]
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	5-10	271-846-8	Xi; R36/38 R43 N; R51/53	[1]
See section 16 for the full text of the R- phrases declared above					

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Date of issue : 1

3. COMPOSITION/INFORMATION ON INGREDIENTS

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

<u>First-aid measures</u>	
Inhalation	: Get medical attention if adverse health effects persist or are severe.
Ingestion	 Do not induce vomiting unless directed to do so by medical personnel. Maintain an open airway. Seek immediate medical attention.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Obtain medical attention if symptoms occur.
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Notes to physician	 No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
o	

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	ep unnecessary and unprotected personnel from entering. Do not ough spilt material. Put on appropriate personal protective equipm	
Environmental precautions	oid dispersal of spilt material and runoff and contact with soil, wate d sewers. Inform the relevant authorities if the product has caused llution (sewers, waterways, soil or air). Water polluting material. M e environment if released in large quantities.	environmental
Large spill	op leak if without risk. Move containers from spill area. Prevent en ter courses, basements or confined areas. Wash spillages into an atment plant or proceed as follows. Contain and collect spillage w mbustible, absorbent material e.g. sand, earth, vermiculite or diato d place in container for disposal according to local regulations (see	effluent ith non- maceous earth
Small spill	op leak if without risk. Move containers from spill area. Absorb with aterial and place in an appropriate waste disposal container.	n an inert

7. HANDLING AND STORAGE

Handling	: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.
Storage	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
Packaging materials Recommended	: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values		
Ingredient name		Occupational exposure limits
No exposure limit value known		
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.
Exposure controls		
Occupational exposure controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
Respiratory protection	:	No special measures required.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.
Eye protection		Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information Appearance Form : Liquid. Colour : Blue. Odour : Faint odour. Important health, safety and environmental information Flash point : Closed cup: >101°C (>213.8°F) Density : ~1.1 g/cm³ [20°C (68°F)] Solubility : Insoluble in the following materials: water

Viscosity : Dynamic: 1900 to 2600 mPa·s (1900 to 2600 cP)

10. STABILITY AND REACTIVITY

Stability	:	The product is stable.
Conditions to avoid	:	Avoid release to the environment. Refer to special instructions/safety data sheet.
Materials to avoid	:	No specific data.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation	ay cause irritation.	
Ingestion	tating to mouth, throat and stomach.	
Skin contact	tating to skin. May cause sensitisation by skin contact.	
Eye contact	tating to eyes.	
Chronic effects	nce sensitized, a severe allergic reaction may occur when subsequ ry low levels.	ently exposed to

12. ECOLOGICAL INFORMATION

Environmental effects : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
European waste catalogue (EWC)	: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Packaging	:

13. DISPOSAL CONSIDERATIONS

Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

ADR	
UN number	: UN3082
ADR Class	: 9
Classification code	: M6
Packing group	: III
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.
Contains	: Epoxide resin
Label No.	: 9
IMDG	
UN number	: UN3082
IMDG Class	: 9
Packing group	: III
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.
Contains	: Epoxide resin
Emergency schedules (EmS)	: F-A, S-F
Marine pollutant	: P
Label no.	: 9
IATA	
UN number	: UN3082
IATA Class	: 9
Packing group	: III
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.
Contains	: Epoxide resin
Label no.	: 9

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols	: Xi, N
	Irritant, Dangerous for the environment
Contains	 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700) reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)
	oxirane, mono[(C12-14-alkyloxy)methyl]derivs

Date of issue	: 16.03.2009.	MSDS no. : 111319	5/6
---------------	---------------	-------------------	-----

15. REGULATORY INFORMATION

Risk phrases	:	R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	:	S24- Avoid contact with skin. S37- Wear suitable gloves.
Additional warning phrases	:	Contains epoxy constituents. See information supplied by the manufacturer.
VOC content (EU)	:	VOC (w/w): 0.02%
National regulations		
Regulatory information	:	Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP 3)
		Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as amended)
		Health & Safety at Work Act 1974
		The Environmental Protection (Duty of Care) Regulations 1991 Hazardous waste regulations 2005
		The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007
Guidance Publications	:	Approved Code of Practice - Management of Health and Safety at Work, HSE General Approved Code of Practice to COSHH Regulations, HSE.

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and 3	:	R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Full text of classifications referred to in sections 2 and 3	:	Xi - Irritant N - Dangerous for the environment

<u>History</u>				
Date of printing	:	16.03.2009.		
Date of issue	:	16.03.2009.		
Date of previous issue	:	No previous validation.		
$oldsymbol{\mathbb{F}}$ Indicates information that has changed from previously issued version.				

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

Jika

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name :

Sika Primer-MB, Part B

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ United Kingdom
Telephone no.	:	01707 394444
Fax no.	:	01707 329129
e-mail address of person responsible for this SDS	:	EHS@uk.sika.com
Emergency telephone number	:	-

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	; R20/21/22 R35 3 2/53	
Human health hazards	rmful by inhalation, in contact with skin and if swallowed. Causes severe by cause sensitisation by skin contact.	burns.
Environmental hazards	rmful to aquatic organisms, may cause long-term adverse effects in the a vironment.	aquatic

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ Characteristics

: Modified polyamine

Ingredient name	CAS number	%	EC number	Classification	
benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine	100-51-6 2855-13-2	35-50 10-25	202-859-9 220-666-8	Xn; R20/22 Xn; R21/22 C; R34 R43 R52/53	[1] [1]
m-phenylenebis(methylamine)	1477-55-0	10-20	216-032-5	Xn; R20/22 C; R35 R43 R52/53	[1] [2]
3,6,9-triazaundecamethylenediamine	112-57-2	5-10	203-986-2	Xn; R21/22 C; R34 R43 N; R51/53	[1]
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	5-7	202-013-9	Xn; R22 Xi; R36/38	[1]
2-Propenenitrile, reaction products with 2,2,4(or	90530-20-4	3-5	292-059-6	Xn; R22	[1]
Date of issue : 16.03.2009.			MSDS no. : 2	23916	1/

2/7

3. COMPOSITION/INFORMATION ON INGREDIENTS

2,4,4)-trimethyl-1,6-hexanediamine				C; R34 R43 N; R51/53	
Trimethylhexane-1,6-diamine	25620-58-0	1-2.5	247-134-8	Xn; R22 C; R34 R43 R52/53	[1]
See section 16 for the full text of the R- phrases declared above					

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures	
Inhalation	: Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.
Ingestion	: Get medical attention immediately. Do not induce vomiting unless directed to do so by medical personnel. Chemical burns must be treated promptly by a physician. Maintain an open airway.
Skin contact	: Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Eye contact	: Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	 Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

 Date of issue
 : 16.03.2009.
 MSDS no.
 : 23916

ACCIDENTAL RELEASE MEASURES 6.

Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

HANDLING AND STORAGE 7.

Handling	: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous.
Storage	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
Packaging materials	
Recommended	: Use original container.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

Exposure limit values

Ingredient name		Occupational exp	oosure limits	
No exposure limit value known.				
Recommended monitoring procedures	:	atmosphere or biological monitoring of the ventilation or other control me protective equipment. Reference sh methods for the assessment of expo	with exposure limits, personal, workplace may be required to determine the effectiveness easures and/or the necessity to use respiratory hould be made to European Standard EN 689 for osure by inhalation to chemical agents and ethods for the determination of hazardous	
Exposure controls				
Occupational exposure controls	:	vapour or mist, use process enclosu	If user operations generate dust, fumes, gas, ires, local exhaust ventilation or other engineerir airborne contaminants below any recommende	
Hygiene measures	:	eating, smoking and using the lavate	roughly after handling chemical products, befor bry and at the end of the working period. sed to remove potentially contaminated clothing reusing.	
Respiratory protection	:	No special measures required.		
Hand protection	:		es complying with an approved standard should chemical products if a risk assessment indicates Butyl rubber/nitrile rubber gloves.	
Eye protection	:		pproved standard should be used when a risk ary to avoid exposure to liquid splashes, mists,	
Date of issue	:	16.03.2009.	MSDS no. : 23916	3/7

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Skin protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information			
<u>Appearance</u>			
Form :	Liquid.		
Colour :	Yellowish.		
Odour :	Amine-like.		
Important health, safety and environmental information			
pH :	12		
Flash point :	Closed cup: >101°C (>213.8°F)		
Density :	~1.018 g/cm ³ [23°C (73.4°F)]		
Solubility :	Insoluble in the following materials: water		
Viscosity :	Dynamic: 12 mPa·s (12 cP)		

10. STABILITY AND REACTIVITY

Stability	:	e product is stable.			
Conditions to avoid	:	No specific data.			
Materials to avoid	:	Reactive or incompatible with the following materials: acids			
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation	 Harmful by inhalation. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. May cause irritation.
Ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.
Skin contact	 Severely corrosive to the skin. Causes severe burns. Harmful in contact with skin. May cause sensitisation by skin contact.
Eye contact	: Severely corrosive to the eyes. Causes severe burns.
Chronic effects	 Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

12. ECOLOGICAL INFORMATION

Environmental effects

: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
European waste catalogue (EWC)	:	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Packaging	:	Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.
		Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.
		Any disposal practice must be in compliance with local and national laws and regulations.
		15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

ADR		
UN number	:	UN1760
ADR Class	:	8
Classification code	:	C9
Packing group	:	II
Proper shipping name	:	Corrosive liquid, n.o.s.
Contains	:	Isophoronediamine, Xylylenediamine
Label No.	:	8
<u>IMDG</u>		
UN number	:	UN1760
IMDG Class	:	8
Packing group	:	II
Proper shipping name	:	Corrosive liquid, n.o.s.
Contains	:	Isophoronediamine, Xylylenediamine
Emergency schedules (EmS)	:	F-A, S-B
Marine pollutant	:	No.
Label no.	:	8
IATA		
UN number	:	UN1760
IATA Class		8
Packing group	-	1
Proper shipping name	:	Corrosive liquid, n.o.s.
Contains		Isophoronediamine, Xylylenediamine
Label no.	÷	8
	•	0

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols					
	prrosive				
Contains	benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) 3,6,9-triazaundecamethylenediamine 2-Propenenitrile, reaction products with 2,2,4(or 2,4,4)-trimethyl-1,6- hexanediamine Trimethylhexane-1,6-diamine				
Risk phrases	20/21/22- Harmful by inhalation, in contact with skin and if swallowed. 35- Causes severe burns. 43- May cause sensitisation by skin contact. 52/53- Harmful to aquatic organisms, may cause long-term adverse effects in uatic environment.	n the			
Safety phrases	26- In case of contact with eyes, rinse immediately with plenty of water and seedical advice. 36/37/39- Wear suitable protective clothing, gloves and eye/face protection. 45- In case of accident or if you feel unwell, seek medical advice immediately e label where possible).				
VOC content (EU)	DC (w/w): 48%				
National regulations					
Regulatory information	nemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP			
	ontrol of Substances Hazardous to Health Regulations 2002 (COSHH) (as nended) ealth & Safety at Work Act 1974 ne Environmental Protection (Duty of Care) Regulations 1991 azardous waste regulations 2005 ne Carriage of Dangerous Goods and Use of Transportable Pressure Equipm egulations 2007	nent			
Guidance Publications	pproved Code of Practice - Management of Health and Safety at Work, HSE eneral Approved Code of Practice to COSHH Regulations, HSE.				

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and 3	 R22- Harmful if swallowed. R20/22- Harmful by inhalation and if swallowed. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R21/22- Harmful in contact with skin and if swallowed. R34- Causes burns. R35- Causes severe burns. R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Full text of classifications referred to in sections 2 and 3	C - Corrosive Xn - Harmful Xi - Irritant N - Dangerous for the environment

Date of issue	: 16.03.2009.	MSDS no. : 23916	6/7
---------------	---------------	-------------------------	-----

16. OTHER INFORMATION

<u>History</u>		
Date of printing	:	16.03.2009.
Date of issue	:	16.03.2009.
Date of previous issue	:	No previous validation.
$oldsymbol{\mathbb{V}}$ Indicates information that has changed from previously issued version.		

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.